

DH-HCVR7204/7208A


4/8 All Channel 1080P 1U HDCVI DVR



Features

- Up to 4/8 cameras with 1080p realtime preview
- H.264 dual-stream video compression
- HCVR7204/7208A: All channel 1080P
- HDMI / VGA / TV simultaneous video output
- 4/8 channel synchronous playback, GRID interface & smart search
- 3D intelligent positioning with Dahua PTZ dome camera
- Support 2 SATA HDD up to 8TB, 2 USB2.0
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

System Connection



* Takes HCVR7208A as an example

Technical Specifications

Model	DH-HCVR7204A	DH-HCVR7208A
System		
Main Processor	Embedded processor	
Operating System	Embedded LINUX	
Video		
Input	4 channel, BNC	8 channel, BNC
Standard	NTSC(525Line, 60f/s), PAL(625Line, 50f/s)	
Audio		
Input	4 channel, BNC	
Output	1 channel, BNC	
Two-way Talk	Reuse audio input/output channel 1	
Display		
Interface	1 HDMI, 1 VGA, 1BNC	
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768, 800×600	
Display Split	1/4	1/4/8/9
Privacy Masking	4 rectangular zones (each camera)	
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording	
Recording		
Video/Audio Compression	H.264 / G.711	
Resolution	1080P(1920×1080/1920×900)/(720P(1280×720/1280×600)/960H(960×576/960×480)/D1/4CIF(704×576/704×480)/CIF(352×288/352×240)/QCIF(176×144/176×120)	
Record Rate	Main stream	1080P/720P/960H/D1/HD1/2CIF/CIF(1~25/30fps)
	Extra stream	CIF/QCIF(1~25/30fps)
Bit Rate	48~8192Kb/s	
Record Mode	Manual, Schedule(Regular(Continuous), MD), Stop	
Record Interval	1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec	
Video Detection & Alarm		
Trigger Event	Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips	
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank	
Alarm Input	4 channel	8 channel
Relay Output	3 channel	
Playback & Backup		
Sync Playback	1/4	1/4/8
Search Mode	Time/Date, MD & Exact search (accurate to second)	
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom	
Backup Mode	USB Device / Network	
Network		
Ethernet	RJ-45 port (10/100M/1000M)	
Network Functions	HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPoE, DDNS, FTP, IP Filter	
Max. User Access	128 users	
Smart Phone	iPhone, iPad, Android, Windows Phone	
Storage		
Internal HDD	2 SATA port, up to 8TB	
Auxiliary Interface		
USB Interface	2 ports (1 Rear), USB2.0	
RS232	1 port, For PC communication & Keyboard	
RS485	1 port, For PTZ control	
General		
Power Supply	DC12V/5A	
Power Consumption	15W(without HDD)	
Working Environment	-10 ~ +55°C / 10~90%RH / 86~106kpa	
Dimension(W×D×H)	1U, 375mm×285mm×45mm	
Weight	2.35kg (without HDD)	